

RAL8001

SKT360M10

360 Watt

182mm 108Cells Double Glass Bifacial Terracotta
N Type Mono Half Cell PV Module Series



Terracotta
glass and frame



Suitable for red / orange
/ terracotta roof buildings



PV facade with
innovative compositions



SMBB Technology
Half Cut N Type Cell



Anti PID



Excellent Low-light
Performance



100% Inspection
Guarantee Reliability



Strengthened
Mechanical Load




SCAN CODE TO
WATCH VIDEO







Learn more about the
production of 182mm
Mono PV Solar Module



Sunket N Type Linear Warranty





All Dimensions in mm
The above drawing is a graphical representation of the product.

Transparent backsheet is available.
Bifacial Solar PV Modules can be customized.

Electrical Characteristics (STC)

Module Type	SKT360M10
Test Conditions	STC
Maximum Power- Pmax(W)	360
Open Circuit Voltage - Voc(V)	38.91
Short- Circuit Current - Isc(A)	11.58
Voltage at Pmax -Vmp(V)	33.56
Current at Pmax - Imp(A)	10.73
Module Efficiency - η m(%)	18.4
Power Tolerance(W)	(0, +4.99W)
Maximum System Voltage(V)	1500Vdc (IEC / UL)
Maximum Series Fuse Rating (A)	25A

*STC : Irradiance 1000W/m², Cell Temperature 25 °C, Air Mass 1.5

*Measurement tolerance: ±3% *Power binning up to: +3%

Mechanical Specifications

External Dimensions	1722x1134x30mm
Weight	23.4kg
Solar Cells	Mono crystalline 182mm (2x54pcs)
Glass	AR Coated 2+2 mm tempered glass
Frame	Anodized aluminum alloy
Junction Box	IP68
Output Cables	4.0mm ² , 1200mm (+), 1200mm (-), length can be customized
Connector	MC4 Compatible
Mechanical Load	Front Side Max. 5400Pa, Rear Side Max. 2400Pa

Packing Configuration

Pallet Dimensions	1750×1140×1254mm		
Ways of Transport	40'HQ	13.5m Flatbed Truck	17.5m Flatbed Truck
Pieces per Pallet	37 Pcs	36 Pcs	36 Pcs
Pallets per Container	26 Pallets	22 Pallets	34 Pallets
Pieces per Container	962 Pcs	792 Pcs	1224 Pcs

Temperature Characteristics

Pmax Temperature Coefficient	-0.290%/°C
Voc Temperature Coefficient	-0.250%/°C
Isc Temperature Coefficient	+0.045%/°C
Operating Temperature Range	-40~+85°C
Nominal Operating Cell Temperature	45±2°C

Current-Voltage & Power-Voltage Curves (SKT360M10)

