



Anti PID



Excellent Low-light Performance



Strengthened Mechanical Load



Advanced Bifacial Efficiency



100% Inspection Guarantee Reliability



SMBB-HJT Half Cut




SKT440~460M12-96D4

440~460 Watt

210x182mm 18BB 96Cells Double Glass Bifacial
HJT Mono Half Cell PV Module Series


Sunket linear Warranty



 **SUNKET® - Solar**

SKT440~460M12-96D4

210x182mm 18BB 96Cells Double Glass Bifacial
HJT Mono Half Cell PV Module Series



All Dimensions in mm
The above drawing is a graphical representation of the product.

Electrical Characteristics (STC/BSTC)

Module Type	SKT440M12-96D4		SKT445M12-96D4		SKT450M12-96D4		SKT455M12-96D4		SKT460M12-96D4	
Test Conditions	STC	BSTC	STC	BSTC	STC	BSTC	STC	BSTC	STC	BSTC
Maximum Power- Pmax(W)	440	490	445	495	450	500	455	505	460	510
Open Circuit Voltage - Voc(V)	36.68	36.68	36.95	36.95	37.22	37.22	37.47	37.47	37.72	37.72
Short- Circuit Current - Isc(A)	15.26	17.01	15.30	17.05	15.36	17.12	15.41	17.17	15.45	17.22
Voltage at Pmax -Vmp(V)	30.43	30.43	30.66	30.66	30.88	30.88	31.10	31.10	31.30	31.30
Current at Pmax - Imp(A)	14.47	16.11	14.53	16.15	14.60	16.19	14.66	16.24	14.72	16.30
Module Efficiency -ηm(%)	22.02	/	22.27	/	22.52	/	22.77	/	23.02	/

Power Tolerance(W)	(0, +4.99W)									
Maximum System Voltage(V)	1500Vdc (IEC / UL)									
Maximum Series Fuse Rating (A)	30A									

*STC : Irradiance 1000W/m², Cell Temperature 25℃, Air Mass 1.5
*BSTC : Front side irradiation 1000W/m², back side reflection irradiation 135W/m², AM=1.5, Ambient Temperature 25℃.
*Measurement tolerance: ±3% *Power binning up to: +3%

Mechanical Specifications

External Dimensions	1762x1134x30mm
Weight	24kg
Solar Cells	HJT 182x105mm (2x48pcs)
Glass	AR Coated 2+2 mm tempered glass
Frame	Anodized aluminum alloy
Junction Box	IP68
Output Cables	4.0mm², 1200mm (+), 1200mm (-), length can be customized
Connector	MC4 Compatible
Mechanical Load	Front Side Max. 5400Pa, Rear Side Max. 2400Pa

Packing Configuration

Pallet Dimensions	1790x1140x1254mm		
Ways of Transport	40'HQ	13.5m Flatbed Truck	17.5m Flatbed Truck
Pieces per Pallet	37 Pcs	36 Pcs	36 Pcs
Pallets per Container	26 Pallets	22 Pallets	33 Pallets
Pieces per Container	962 Pcs	792 Pcs	1188 Pcs

Temperature Characteristics

Pmax Temperature Coefficient	-0.260%/℃
Voc Temperature Coefficient	-0.240%/℃
Isc Temperature Coefficient	+0.040%/℃
Operating Temperature Range	-40~+85℃
Nominal Operating Cell Temperature(BSTC)	44±2℃

Current-Voltage & Power-Voltage Curves (SKT460M12-96D4)

