

N TYPE

SCAN CODE TO
WATCH VIDEO




Learn more about the
production of 182mm
Mono PV Module

SKT510~530M10-132D4 510~530 Watt

182mm 16BB 132Cells Double Glass Bifacial
N Type Mono Half Cell PV Module Series

Sunket N Type Linear Warranty



SMBB Technology
Half Cut N Type Cell



High Energy
Performance



100% Inspection
30years Guarantee



Fire Class A




5400Pa
Strengthened
Mechanical Load



Advanced Bifacial
Efficiency




 **SUNKET[®] - Solar**



All Dimensions in mm
The above drawing is a graphical representation of the product.

Current-Voltage & Power-Voltage Curves (SKT530M10-132D4)



Electrical Characteristics (STC/NOCT)

Module Type	SKT510M10-132D4		SKT515M10-132D4		SKT520M10-132D4		SKT525M10-132D4		SKT530M10-132D4	
Test Conditions	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power- Pmax(W)	510	386	515	389	520	393	525	397	530	401
Open Circuit Voltage - Voc(V)	46.31	44.10	46.50	44.29	46.69	44.48	46.88	44.67	47.07	44.86
Short- Circuit Current - Isc(A)	14.04	11.32	14.10	11.37	14.16	11.42	14.22	11.47	14.28	11.51
Voltage at Pmax -Vmp(V)	38.44	36.35	38.64	36.43	38.84	36.60	39.04	36.76	39.24	36.93
Current at Pmax - Imp(A)	13.27	10.62	13.33	10.68	13.39	10.74	13.45	10.80	13.51	10.86
Module Efficiency -ηm(%)	21.48	/	21.69	/	21.90	/	22.11	/	22.32	/
Power Tolerance(W)	(0, +4.99W)									
Maximum System Voltage(V)	1500Vdc (IEC / UL)									
Maximum Series Fuse Rating (A)	30A									

*STC : Irradiance 1000W/m², Cell Temperature 25 °C, Air Mass 1.5

*NOCT : Irradiance 800W/m², Ambient Temperature 20 °C, Air Mass 1.5, Wind Speed 1m/s

*Measurement tolerance: ±3% *Power binning up to: +3%

Mechanical Specifications

External Dimensions	2094×1134×30mm
Weight	27.3kg
Solar Cells	N-Type 16BB 182mm (2×66pcs)
Glass	AR Coated 2+2 mm tempered glass
Frame	Anodized aluminum alloy
Junction Box	IP68
Output Cables	4.0mm², 1200mm (+), 1200mm (-), length can be customized
Connector	MC4 Compatible
Mechanical Load	Front Side Max. 5400Pa, Rear Side Max. 2400Pa

Temperature Characteristics

Pmax Temperature Coefficient	-0.290%/°C
Voc Temperature Coefficient	-0.250%/°C
Isc Temperature Coefficient	+0.045%/°C
Operating Temperature Range	-40~+85°C
Nominal Operating Cell Temperature(NOCT)	45±2°C

Bifacial Output Rear Side Power Gain

*Take SKT520M10-132D4 as an example.

Power Gain	10%	15%	20%	25%	30%
Maximum Power- Pmax(W)	572.0	598.0	624.0	650.0	676.0
Open Circuit Voltage - Voc(V)	46.69	46.69	46.69	46.69	46.69
Short- Circuit Current - Isc(A)	15.58	16.28	16.99	17.70	18.41
Voltage at Pmax -Vmp(V)	38.83	38.83	38.83	38.83	38.83
Current at Pmax - Imp(A)	14.73	15.40	16.08	16.74	17.41

Packing Configuration

Pallet Dimensions	2125×1140×1254mm		
Ways of Transport	40'HQ	13.5m Flatbed Truck	17.5m Flatbed Truck
Pieces per Pallet	37 Pcs	36 Pcs	36 Pcs
Pallets per Container	22 Pallets	20 Pallets	29 Pallets
Pieces per Container	814 Pcs	720 Pcs	1044 Pcs