

N TYPE

SCAN CODE TO
WATCH VIDEO




Learn more about the
production of 182mm
Mono PV Module

SKT580~590M10 580~590 Watt

182mm 16BB 144Cells
N Type Mono Half Cell PV Module Series

Sunket N Type Linear Warranty



SMBB Technology
Half Cut N Type Cell



High Energy
Performance



100% Inspection
25years Guarantee



Fire Class A




Strengthened
Mechanical Load




Anti PID



 **SUNKET[®] - Solar**



All Dimensions in mm
The above drawing is a graphical representation of the product.



Transparent backsheet is available.
Bifacial Solar PV Modules can be customized.

Electrical Characteristics (STC/NOCT)

Module Type	SKT580M10		SKT585M10		SKT590M10	
Test Conditions	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power- Pmax(W)	580	436	585	440	590	444
Open Circuit Voltage - Voc(V)	51.47	48.89	51.67	49.08	51.87	49.27
Short- Circuit Current - Isc(A)	14.37	11.21	14.43	11.26	14.49	11.31
Voltage at Pmax -Vmp(V)	42.60	39.86	42.76	39.97	42.92	40.08
Current at Pmax - Imp(A)	13.62	10.94	13.69	11.01	13.75	11.08
Module Efficiency -ηm(%)	22.45	/	22.64	/	22.84	/
Power Tolerance(W)	(0, +4.99W)					
Maximum System Voltage(V)	1500Vdc (IEC / UL)					
Maximum Series Fuse Rating (A)	30A					

*STC : Irradiance 1000W/m², Cell Temperature 25℃, Air Mass 1.5

*NOCT : Irradiance 800W/m², Ambient Temperature 20℃, Air Mass1.5, Wind Speed 1m/s

*Measurement tolerance: ±3% *Power binning up to: +3%

Mechanical Specifications

External Dimensions	2278×1134×35mm
Weight	28.6kg
Solar Cells	N-Type 16BB 182mm (2×72pcs)
Front Glass	AR Coated 3.2 mm tempered glass
Frame	Anodized aluminum alloy
Junction Box	IP68
Output Cables	4.0mm ² ,1200mm (+), 1200mm (-), length can be customized
Connector	MC4 Compatible
Mechanical Load	Front Side Max. 5400Pa, Rear Side Max. 2400Pa

Temperature Characteristics

Pmax Temperature Coefficient	-0.290%/°C
Voc Temperature Coefficient	-0.250%/°C
Isc Temperature Coefficient	+0.045%/°C
Operating Temperature Range	-40~+85°C
Nominal Operating Cell Temperature(NOCT)	45±2°C

Packing Configuration

Pallet Dimensions	2320×1125×1254mm		
Ways of Transport	40'HQ	13.5m Flatbed Truck	17.5m Flatbed Truck
Pieces per Pallet	31 Pcs	31 Pcs	31 Pcs
Pallets per Container	20 Pallets	21 Pallets	31 Pallets
Pieces per Container	620 Pcs	651 Pcs	961 Pcs

Current-Voltage & Power-Voltage Curves (SKT590M10)

