


225 Watt

SKT 225M10

225瓦单晶光伏组件

182mm 56Cells PV Module



Electrical Characteristics

电气特性

组件型号	Module Type	SKT 225M10
		STC
额定功率	Maximum Power- Pmax(W)	225
开路电压	Open Circuit Voltage - Voc(V)	19.54
短路电流	Short- Circuit Current - Isc(A)	14.78
工作电压	Voltage at Pmax -Vmp(V)	17.14
工作电流	Current at Pmax - Imp(A)	13.13
组件效率	Module Efficiency -ηm(%)	22.11
功率公差	Power Tolerance(W)	0, +4.99W
最高系统电压	Maximum System Voltage(V)	1000Vdc (IEC / UL)
最大额定熔断电流	Maximum Series Fuse Rating (A)	20A

标准测试条件STC：光照强度Irradiance 1000W/m²，组件温度Cell Temperature 25℃，大气质量AM 1.5

Mechanical Specifications

结构特性

组件尺寸	External Dimensions	1330*765*30mm
重量	Weight	11.2kg
电池	Solar Cells	Mono crystalline 182x91mm (4x14pcs)
玻璃	Front Glass	3.2 mm tempered glass
边框	Frame	Aluminum
接线盒	Junction Box	IP67
输出导线	Output Cables	100cm, length can be customized
连接器	Connector	MC4 Compatible
机械载荷	Mechanical Load	Front Side Max. 5400Pa, Rear Side Max. 2400Pa

Temperature Characteristics

温度特性

最高功率温度系数	Pmax Temperature Coefficient	-0.290%/℃
开路电压温度系数	Voc Temperature Coefficient	-0.230%/℃
短路电流温度系数	Isc Temperature Coefficient	+0.050%/℃
光伏组件工作温度	Operating Temperature	-40~+85℃
额定工作电池片温度	Nominal Operating Cell Temperature(NOCT)	45±2℃

Packing Configuration

包装方式

组件型号	Module Type	SKT225M10
组件尺寸	Module Dimensions	1330*765*30mm
托盘尺寸	Pallet Dimensions	1355x1140x80mm
每托重量	Pallet Weight	455kg
每托数量	Pieces/Pallet	37pcs

